

SU-25.6V 120Ah

LiFePO4 Battery

HBL's SU – Series deep cycle rechargeable lithium batteries are highly reliable, long-lasting, and provide more power than the traditional Lead Acid batteries. The lithium battery packs are compact, lightweight, and easy to install. The quick charge and discharge capability make it an ideal choice for backup applications.



Key Features

- ⦿ High quality LFP cells
- ⦿ High rate charge/discharge current @ 1C/1C
- ⦿ Long design life up to 15+years @25°C
- ⦿ High efficiency between charge and discharge
- ⦿ Cell Protection using fixed PCM

Specification

Model		HBL-iON-25.6V-120Ah
Electrical Characteristics	Nominal Voltage	25.6V
	Nominal Capacity	120Ah @ 0.2C Rate to ECV of 2.5V
	Energy	3072Wh
	Cycle Life	≥3000 cycles @80% DOD, 25°C
	Self-Discharge (28 days)	≤3%, @25°C
	Efficiency of charge	≥98%
	Efficiency of Discharge	≥98%@ 0.2C to ECV of 2.5V ≥96%@ 0.5C"
Charge	Charge Voltage	29.2V±0.1V
	Charging Method	Charge current of 0.2C up to 29.2V, then 0.02c after reaching 29.2V (CC/CV)
	Max. Charge Current	120A (1C)
	Charge Cut-off Voltage	30V±0.2V
Discharge	Max. Continuous Discharge Current	120A (1C)
	Discharge Cut-off Voltage	18.4V±0.2V
Environmental	Charge Temperature Range	0°C to 45°C
	Discharge Temperature Range	-20°C to +60°C
	Optimum Operation Temperature	20°C to 25°C
	Storage Temperature	-20°C to +25°C
	Humidity	5%≤RH≤85%
	Ingress protection rating	-
Mechanical	Box	Heat shrinkable sleeve Packing/ MS enclosure (Optional)
	Dimensions (W*D*H) in mm	L:438mm, W:405mm, H:167mm
	Weight(kgs)	40
BMS / PCM	Protection	Over Voltage, Under Voltage, Short Circuit, Over Temperature, Over Charge current, Over Discharge current

*Note: Features and Specifications are subject to change without notice due to continual improvement in technology